

RACK AND CABINET PRODUCT

WALL CABINET



FEATURE

- Exquisite design with precise dimension and craftsmanship.
- International popular smoky-gray glass front door.
- Easily be mounted on wall, or placed on floor after installed castor or feet.
- Loading capacity: 60KG.
- Top and bottom wiring channel could be closed.
- Removable front door and side panel, easily installing and maintaining
- Surface finish: Degreased, acid cleaned, phosphoric, water cleaned, electro-static powder coating, meet ROHS standard.
- Optional color: black/gray
- Optional accessories

MATERIALS

Galvanized Cool rolled steel

Thickness: Vertical rail: 2mm

Else in 1.2mm

Tempered smoky-gray glass with thickness of 5mm.

Electro static powder coating.

Including green-yellow ground wire size 2.5mm.

APPLICATION

Widely used in network system, educational system, broadcasting system and telecommunication system. Suitable for placing server computer and precision electronic equipment.

STANDARD

Comply with ANSI/EIARS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92 standard, IEC 60297, ANSI/EIA-310D-1992(Rev, EIA-310-C) , IEC 60297-1, IEC 60927-2Compatible with metric ETSI and 19 inch international standard, ROHS standard.

FIXED MODEL (WCF)



SWING MODEL (WCS)



PERFEORRATE MODEL (WCP)



ORDER INFORMATION

= Fixed Model

= Swing Model

= Perfeorrate Model

(Capacity)

12U (H = 64 cm)

9U (H = 51 cm)

6U (H = 38 cm)

(Depth)

40 = 400mm

50 = 500mm

60 = 600mm

COLOR

BB =  Black(RAL9004)

BG =  Gray(RAL7044)

