

SFP MODULE SYSTEM PRODUCTS

155M-2.67G CWDM SFP



DESCRIPTION

155M/1.25G/2.5G SFP include CWDM/DWDM series,complaint with MSA,SFF-8472,with the feature of low power consumption,commerical or industrial operation temperature and high reliability,suitable for DC, Metro and Transmission networks.

FEATURE

- Class 1 laser product EN 60825-1 standards
- Operating data rate up to 2.67Gbps
- Compliant with SFP MSA and SFF-8472
- Compliant with SDH/SONET
- Duplex LC connector
- Hot pluggable
- 3.3V Single Power Supply



SPECIFICATIONS

- Fiber Channel
- ATM Switches and Routers
- SONET / SDH Switch
- Fast Ethernet
- Giga Ethernet
- CWDM/DWDM networks
- Ring topologies with fixed and
- Reconfigurable OADMs
- Other optical link

ORDER INFOMATION

Model	Rate	Wavelength	Distance	Optical power	Sensitivity	Other
MC-SFP-CWDM-SM-01xx	155M	1270~1610nm	80 km	-5~-0dBm	<-34dBm	2xLC/SMF
MC-SFP-CWDM-SM-02xx	1.25G	1270~1610nm	80 km	0~-5dBm	<-24dBm	2xLC/SMF
MC-SFP-CWDM-SM-03xx	2.5G	1270~1610nm	80 km	0~-5dBm	<-28dBm	2xLC/SMF

Notes

1. xx refers to CWDM Wavelength range 1270nm to 1610nm, xx=27~61 means 1270nm to 1610nm
2. Wavelengths from 1270nm to 1610nm, each step 20nm