



Delegate Discussion & Voting Unit

TS-0622A



Feature:

- * Unique patented technology, specially designed anti-RF radio frequency interference tube, which can completely eliminate the noise, Showing a perfect high-level conference environment.
- * Unique patented appearance, delicate and modernize.
- * Special microphone head design, even without cotton cover, it can also eliminate the low frequency impact sound.
- * Professional heart-shaped capacitor microphone core; with high sensitivity and clear voice; with red and green annular indicator light.
- * When the red ring light is on, it means somebody is speaking; when green is on, it means apply for awaiting speech.
- * It has function of suppress squeal, when microphone is open, the built-in speaker will be closed automatically.
- * Built-in speaker, headset jack, which can adjust the headset volume.
- * Use the professional 8 core aviation plug by cascading units, and with the metal fixed nut to avoid loosing and falling.
- * It has 1.8 meter 8 core connection line that is used full line of aluminum foil and waterline shield, which greatly reduce the interference of strong electromagnetic waves on the wire, to avoid noise.
- * The address code of each unit can be adjusted at any time to facilitate the construction.
- * It is passive equipment, which is powered by the system controller, input voltage is 24V, within safe scope.
- * Chairman unit is not limited by the quantity of speakers.
- * Chairman unit has priority function of taking full control of the order of the meeting, can approve or reject the application for a delegate unit.
- * The Chairman unit connection position is not limited; can be connected in any position of circuit.
- * "Hand-in-hand" Cable cascade mode, which is easy to install and maintain.
- * There are 5 multi-functional buttons for voting, election and meeting evaluation.
- * The button indicator has a prompt for real-time voting.
- * Speaking unit can apply or cancel to speak.
- * LCD display can show the operation of the vote, voting mode, to avoid mistakes.

Specifications:

Model	TS-0622A
Microphone type	Heart-shaped directional electret
Frequency response	80Hz~16KHz
Microphone input impedance	1KΩ
Sensitivity	-34±2dB(0dB=1V/Pa,at 1kHz)
Max SPL	100dB (THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max power consumption	2.5W
Headphone load	8-32
Headphone volume	Max 40mW
Headphone interface	3.5mm Headphone monaural jack
Follow standard	IEC60914
Connector	1.8m aviation 8 core cable
Hand-in-hand expansion port	NO
Power supply mode	Controller power supply DC24V
Voting function	5/3 keys to vote
Sign-in function	Button sign-in
Color	Silver
Display	LCD blue screen with white text on blue background
Weight	0.9kg
Microphone height	409mm
Dimension(mm)	225(L)×131(W)×48(H)
Installation Method	Tabletop