FTTH ACCESSORIES PRODUCT

Fast Connector



FEATURES

- Standards of IEC, Telcordia
- 60 seconds installation time
- Can be used 3 times
- Low insertion loss
- Compatible with standard SC connectors;
- Field installable, cost effective, user friendly;
- UPC, APC polishing optional;
- No electricity required;
- FTTH cable, fiber optic cable optional;
- Reliable durable and superior optical performance.







SC Fast Connector APC

PRODUCTION DETAILS

| Fiber Type | SM/MM |
|-------------------|----------------------------|
| Surface polishing | SC/UPC, SC/APC |
| Color | Blue, Green |
| insertion loss | 0.3dB |
| return loss | ≥60dB |
| joint endurance | 10Times |
| Material of shell | ABS |
| Applications | 2.0/3.0 or FTTH patch cord |
| Fiber Diameter | 125um |
| Tensile Strength | >20N |
| Lock Strength | 0.2dB |
| Temperature Cycle | 0.3dB |
| Virbration | 0.2dB |
| Temperature | -40°C~+80°C |

ORDER INFOMATION

| PRODUCT | PART NUMBER |
|-----------------------|-------------|
| SC Fast Connector UPC | F-FC-SC-UPC |
| SC Fast Connector APC | F-FC-SC-APC |





