

GOLDEN H SERIES IR ILLUMINATOR

S-H303-IR

- The H series high power IR illuminator is a top quality LED light source of night illumination with the longest service life.
- Deliver high power infrared light for CCTV & IP camera at night time and improve performance of camera to get clear pictures.
- 50,000 hours lifetime of LED.
- 3/5 years warranty.

Professional Design









- Two stages of constant current circuit avoid LED away from instantly impulse impact when started.
- 50% design margin and accurate constant current circuit drive not only develop excellent performance of LED but maintain whole product a super long life of 10 years.
- Low failure rate of products is guaranteed by the professional in-house optimized independent drouit technology, which has been widely used in the illuminators for more than 5 years.
- Wide edge of silica gel circle and water stop line ensure IP66 waterproof and dustproof level.
- Twice direct cooling heat sink processing enable to increase the cooling coefficient and prolong the service life of the product.
- Patent design hexagonal spherical light sensor more accurately responses ambient brightness and improves accuracy of automatic light control.
- · Flexible angle-adjustable bracket can extend the illuminance range widely.
- Robust cooling fin design is available the illuminator working at -40°C to 50°C.
- · Super energy saving circuit with low electrical power consumption.

Qualified Material

- · Super power dot-matrix IR LED with strong light effect, long service life and low light decline feature.
- High efficient twice optical lens processing achieves 90% of the luminous efficiency.
- . The housing adopts high thermal conductivity aluminum to enhance heat dispersion property.
- Stainless steel bracket and screw ensure low maintenance.

Wide Range of Application

 Recommended for security at ports, railway systems, border, prisons, traffic LRP/ANPR, ITS as well as large public places surveillance.

Basic Function

- To improve performance of the weak light camera and enhancing the picture effects at night
- .Conventional night monitoring
- •The function of video analysis at night
- •Reduce signal noise and other image distortion
- •Reduce the network bandwidth requirements
- •Energy saving by power factor correction
- •Reduce the equipment cost
- •Lower cost of installing and wiring

Viewing Picture at Night





With IR

Without IR



GOLDEN H SERIES IR ILLUMINATOR

Picture











Technical Specification

 LED type
 90 pcs 2W dot-matrix IR LED

 Wavelength
 740nm/850nm/940nm

 voltage
 AC85-265V/DC12V/AC24V

Power consumption 111W(850nm)
Day and night switch Auto
Cable length 1.3meter

Mounting Wall mounting "U" bracket
Temperature -40℃ to 50℃

Grade of protection IP66
Color Black
Housing Aluminium

Panel High light transmittance toughened glass

 Net weight
 12kg

 Gross weight
 13kg

 Dimension
 510*206*117mm

 Packing dimension
 720*400*220mm

Model for Selection

IR distance (850nm) Model Beam angle S-H303E-10-IR 10° - 30° 700m-350m 15° - 45° S-H303-15-IR 400m-240m S-H303-30-IR 30° - 90° 300m-180m S-H303-45-IR 45° - 150° 180m-110m 60° - 180° S-H303-60-IR 110m-90m 5-H303-90-TR 90° - 200° 100m-80m S-H303-120-IR 120° - 230° 90m-65m *IR distance is tested by Sony 1/3 CCD Camera.

To achieve the distance needed, please pay attention to your camera specification and lens before purchase. It is normal phenomenon that distance may vary due to different cameras and lens.

Drawing



