

SILVER SD SERIES IR ILLUMINATOR

- Deliver high power infrared light for CCTV & IP camera at night time and improve performance of camera to get clear pictures.
- · 30.000 hours lifetime of LED.
- · 3 years warranty











- · Two stages of constant current circuit avoid LED away from instantly impulse impact when started.
- · Low failure rate of products is guaranteed by the professional in-house optimized independent circuit technology, which has been widely used in our LED illuminators for more than 5 years
- · Wide edge of silica gel circle and water stop line ensure IP66 waterproof and dustproof level
- Twice direct cooling heat sink processing enable to increase the cooling coefficient and prolong the service life of the product.
- · Patent design hexagonal spherical light sensor more accurately responses ambient brightness and improves accuracy of automatic light control.
- · Flexible angle adjustable bracket can extend the illuminance range widely.
- Robust cooling fin design is available the illuminator working at -40°C to 50°C.
- ' Super energy saving circuit with low electrical power consumption.

- Super power dot-matrix IR LED with strong light effect, long service life and low light decline feature.
- High efficient twice optical lens processing achieves 90% of the luminous efficiency
- The housing adopts high thermal conductivity aluminum to enhance heat dispersion property.
- Stainless steel bracket and screw ensure low maintenance

Recommended for security at ports, railway systems, border, prisons, traffic LRP/ANPR, ITS as well as large public places surveillance.

- ·To improve performance of the weak light camera, thereby enhancing the picture effects at night. -Conventional night monitoring •The function of video analysis at night Reduce signal noise and other image distortion Reduce the network bandwidth requirements
- Energy saving by power factor correction
- Reduce the equipment cost Lower cost of installing and wiring

Viewing picture at night





With IR

Without IR



SILVER SD SERIES IR ILLUMINATOR











40pcs 2W dot-matrix IR LED LED type Wavelength 740nm/850nm/940nm Voltage AC85-265V/DC12V/AC24V

Power consumption 92W(850nm) Day and night switch Auto Cable length

1.3meter Mounting Wall mounting "U" bracket

Temperature -40°C to 50°C Grade of protection IP66 Color Beide Housing Aluminum

High light transmittance toughened glass Panel

Net weight 7.8kg Gross weight 8.5kg Dimension 409*206*117mm Packing dimension 520*400*220mm

Model	Beam angle	IR distance(850nm)
S-S202D-15-IR	15° - 30°	330m-220m
S-S202D-30-IR	30° - 60°	250m-165m
S-S202D-45-IR	45° - 90°	160m-100m
S-S202D-60-IR	60° - 120°	100m-80m
S-S202D-90-IR	90° - 140°	80m-70m
S-S202D-120-IR	120° - 180°	70m-60m

*IR distance is tested by Sony 1/3 CCD Camera. To achieve the distance needed, please pay attention to your camera specification and lens before purchase. It is normal phenomenon that distance may vary due to different cameras and lens.