

Vandal Resistant IR Illuminator

S-SG6-IR IR Illuminator

Deliver high power infrared light for CCTV & IP camera at night time and improve performance of camera to get clear pictures.



Product Features

- Precise secondary optical technology
- The latest LED technology assures outstanding performance of LED with excellent luminous efficiency and more uniform illumination
- Independent innovation of high efficiency power drive schemes
- Low failure rate of products is guaranteed because of professional in-house optimized independent circuit technology widely used in our LED illuminators for more than 5 years
- High thermal conductivity aluminum
- Excellent thermal management not only reduces excess heat and brightness decay of LED but also ensures efficient, reliable and continuous operation of LED throughout its lifetime as 50,000 hours.
- Manual adjustable photo cell and brightness
- Easily set the time of Turn-on illuminator to meet any environmental brightness requirement and dim the brightness of illuminator to suitable light effect.
- Vandal resistant
- Vandal resistant panel protects against hammer, stone and continuous thumping in a certain range.
- Energy saving technology
- All illuminators has energy saving circuit with low electrical power consumption.
- Thinner and lighter design
- Our patent owned housing is designed for simple installation and easy operation to reduce construction difficulty.
- Warranty period
- 3 year warranty



Basic Function

- To improve performance of the weak light camera, thereby enhancing the picture effects at night.
- Conventional night monitoring
- The function of video analysis at night
- Reduce signal noise and other image distortion
- Reduce the network bandwidth requirements
- Energy saving by power factor correction
- Lower cost of installing and wiring
- Indoor and outdoor use

Viewing picture at night



With IR light

Without IR light

Picture



Product Certificate



Technical Specification


LED type: 6 pieces high power IR LED
 Wavelength: 740nm/850nm/940nm
 Beam angle: 15 to 120°
 Beam distance: 80m to 12m(850nm)
 Bracket: wall mount bracket
 Working voltage: DC 12V
 Current: 800mA (adjustable)(850nm)
 Day/night switch: automatic
 Working temperatures: -30 to 50°C
 Protection level: IP65
 Color: black
 Panel: Vandal proof PC panel
 Housing: aluminum die-casting housing
 N.W.: 0.53KG
 G.W.: 0.8KG
 Packing dimension: 145*135*95mm

Adjustment and installation



This side must be downward!

Drawing



Model for Selection

Model	Beam angle	IR Distance(850nm)
S-SG6-15-C-IR	15°	80m
S-SG6-30-C-IR	30°	60m
S-SG6-45-C-IR	45°	40m
S-SG6-60-C-IR	60°	22m
S-SG6-90-C-IR	90°	16m
S-SG6-120-C-IR	120°	12m

*IR distance is tested by Sony 1/3 CCD Camera with 0.01LX.

To achieve the distance needed, please pay attention to your camera specification and lens before purchase. It is normal phenomenon that distance may vary due to different cameras and lens.