

HDMI Extender Series

User Manual

Model: HEOIC

HDMI over Coaxial Extender 1080p 100M




Introduction

HE01C is an HDMI extender that can use a coaxial cable to send HDMI signal with a transmission distance of up to 100M. Its RX unit has a BNC loop-out port to daisy chain for HDMI distribution and extension. For each RX added, you can have one additional HDMI output.

Features

- Resolution up to 1080p.
- Signal extension up to 100M over coaxial cable.
- Built-in BNC loop-out port for daisy chain to have multiple remote HDMI displays.

Installation View



Cable

To send HD video must use coaxial cable with Bandwidth at least 1.5G, to send Full HD video must use coaxial cable with bandwidth at least 3G.

Link cable recommend to use high quality 75Ω Coaxial Cable & BNC connector, to use low quality coaxial cable may case signal loss and effect transmission distance and reliability.

Working Distance

Max. distance via high quality 75Ω Coaxial Cable (Belden 1505A Testing)		
SD (480i,576i resolution) (270Mbps)	300M	
HD (720p, 1080i, 1080p@24/25/30Hz resolution) (1.45Gbps)	200M	
Full HD (1080p@50/60Hz) resolution (2.97Gbps)	100М	

LED Indication

HE01CT

GREEN Power & Signal ON Power on

FLASH Not support HDMI input format

BLUE SDI signal

ON SDI signal output


HE01CR


GREEN Power

BLUE SDI signal lock


Panel View


HE01CT





HE01CR





HE01CT Switch Instruction

- 1 \rightarrow \text{Video Support: 480i, 576i, 720p@50/59.94/60Hz,} \text{Max resolution 1080i@50/59.94/60Hz.}
 - Video Support: 480i, 576i, 720p@50/59.94/60Hz, 1080i@50/59.94/60Hz, Max resolution 1080p@23.98/24/29.97/30/50/59.94/60Hz.
- 2 Audio Support LPCM 2 Channels.
 - ↓ Audio Support LPCM 7.1 Channels.

Specification

ITEM NO.	HE01CT	HE01CR	
Support			
Max. HDMI Resolution	1080p@60Hz		
Max. SDI Resolution	3G-SDI		
Max. Transmission Distance	100M over 1.5G/ 3G Coaxial Cable or Greater		
Audio Format	LPCM 7.1 Channels, 48kHz, 16 / 20 / 24Bit		
Ports & Interfaces			
Video Input	1 x HDMI Type A	1 x 75Ω BNC	
Video Output	1 x 75Ω BNC	1 x HDMI Type A, 1 x 75Ω BNC	
Power			
Power Supply	DC 5V 2A	DC 5V 2A	
Power Consumption	850mA	750mA	
Ambient Temperature			
Operation	0 to 55°C		
Storage	-20 to 85°C		
Humidity	up to 95%		
Physical Characteristics			
Dimensions	67 x 110 x 27mm	67 x 110 x 27mm	
Weight	200g	200g	