

FIBER OPTIC ACCESSORIES

MPO-MPO Truk Cord Female-Female Single-mode/Multimode



FEATURES

- Eliminate termination errors, Min installation time.
- Each cable is 100% tested for low insertion loss and back reflection.
- Optimized performance - Elite MPO and discrete premium connector.
Suitable for MPO application

PERFORMANCE

- Typical Insertion Loss ≤ 0.6 dB
- Typical Return Loss ≥ 20 dB
- Operating Temperature: $-40 \sim +75$ °C
- Storage Temperature: $-40 \sim +85$ °C
- Wavelength 850nm



STANDARD

- Support 40GBASE-SR4 in applicable parallel optics networks.
- Compliant to IEC-61754-7 and TIA-604-5(FOCIS-5) standard.
- Telcordia GR-1435-CORE, and RoHS
- LSZH Jacket by Default

APPLICATION

- Data Centers with High Density Requirement.
- Fiber Channel Storage.
- Parallel Processing Applications.
- Telecommunications and Backbone Installations.

DESCRIPTION

MTP/ MPO Fiber Loopbacks is designed to provide a media of return patch for a fiber optic signal. Typically it is used for fiber optic testing applications or network restorations. For the testing applications, the loopback signal is used for diagnosing a problem. Sending a loopback test to network equipment, one at a time, is a technique for isolating a problem.

ORDER INFORMATION

PRODUCT	PART NUMBER
MPO-MPO Truk Cord Female-Female, MM/OM3, 6.5mm, 12F	F-MPOTR-MM/OM3-6.5MM-12F
MPO-MPO Truk Cord Female-Female, MM/OM4, 6.5mm, 12F	F-MPOTR-MM/OM4-6.5MM-12F
MPO-MPO Truk Cord Female-Female, SM/OS2, 6.5mm, 12F	F-MPOTR-SM/OS2-6.5MM-12F
MPO-MPO Truk Cord Female-Female, MM/OM3, 6.5mm, 24F	F-MPOTR-MM/OM3-6.5MM-24F
MPO-MPO Truk Cord Female-Female, MM/OM4, 6.5mm, 24F	F-MPOTR-MM/OM4-6.5MM-24F
MPO-MPO Truk Cord Female-Female, SM/OS2, 6.5mm, 24F	F-MPOTR-SM/OS2-6.5MM-24F

FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict, Bang Khen District Bangkok 10220

Email : info@focomm-cabling.com www.focomm-cabling.com

